



# 3/8" COMB LIGHT

## PRODUCT INFORMATION

3/8 cell honeycomb core faced with 1/8 HDF.

### SIZES AVAILABLE

- 3/4"x49x97
- 1"x49x97
- 1-1/4"x49x97
- 1-1/2"x49x97
- 1-3/4"x49x97
- 2"x49x97
- 3/4"x49x121
- 1"x49x121
- 1-1/4"x49x121
- 1-1/2"x49x121
- 1-3/4"x49x121
- 2"x49x121

### ADVANTAGES

- This material has been proved to be a great design solution for many applications where strong, lightweight and thick panels are required
- Easily apply face materials (veneer, laminate, and coatings)
- Finish with a variety of edge options
- Rigid face material supports selected methods of attachment
- Optional skin thicknesses are available



## PRODUCT SPECIFICATION

### TECHNICAL DATA

	MATERIAL THICKNESS					
	3/4"	1"	1-1/4"	1-1/2"	1-3/4"	2"
SKIN THICKNESS	0.118"	0.118"	-	0.118"	0.118"	0.118"
CORE THICKNESS	0.514"	0.764"	-	1.264"	1.514"	1.764"
MAX SCREW WITHDRAWN FORCE, LBF	70	-	-	64	-	-
MAX SCREW TENSILE FORCE, LBF	47	-	-	78	-	-
MAX TENSILE STRENGTH, PSI	11	-	-	19	-	-
COMP. STRENGTH @5% STRAIN, PSI	29	-	-	27	-	-
MAX FLEXURE FORCE, LBF	71	-	-	120	-	-
MODULUS OF RUPTURE, PSI	1886	-	-	870	-	-
MODULUS OF ELASTICITY, PSI	214079	-	-	155483	-	-
WEIGHT PER PANEL, LB** ( 49 x 97 )	43	44	-	47	49	51

### PACKAGING QUANTITY PER SKID

SHEET SIZE	MATERIAL THICKNESS					
	3/4"	1"	1-1/4"	1-1/2"	1-3/4"	2"
49 X 97	64	48	38	32	27	24

\* Testing conducted with Varianta Screw HC 013.30.900

\*\* Actual measured weight may vary due to temperature and humidity. Weight provided is for comparative analysis only

